



# TESTORS® CRAFT FABRIC SPRAY PAINT

## DESCRIPTION AND USES

Testors® Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions.

## PRODUCTS

SKU	DESCRIPTION (5 oz. Aerosol)
344357	Matte Black
344359	Matte White
344360	Matte Red
344361	Matte Yellow
344362	Matte Pink
344363	Matte Blue

## PRODUCT APPLICATION

Use in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

## PRODUCT APPLICATION (cont.)

### SURFACE PREPARATION

Remove all dirt, grease, oil, salt and contaminants. Rinse with fresh water and allow to thoroughly dry.

### APPLICATION

Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6"– 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

### DRY TIMES

Dry to the touch in less than 30 minutes, dry to handle in 3 hours, and washable in 3 days.

## PHYSICAL PROPERTIES

		CRAFT FABRIC SPRAY PAINT
Resin		PUD
Pigment		Varies depending on color
Solids By Weight		13.4-17.5%
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	>30 minutes
	Handle	3 hours
	Washable	3 days
Shelf Life		12 months
Flash Point		100°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.