

BASE CONTAINS: XYLENE, METHYL ISOBUTYL KETONE, AND EPOXY RESIN. **ACTIVATOR CONTAINS:** XYLENE AND N-BUTANOL. Vapor harmful. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Causes nose, skin and throat irritation. Avoid prolonged or repeated contact with skin. Harmful if swallowed. Wash thoroughly after handling. Keep away from heat, sparks and flame. **VAPORS MAY CAUSE FLASH FIRE.** Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. In case of eye or skin contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov. **KEEP OUT OF REACH OF CHILDREN.**

BASE CONTIENE: XILENO, METILO ISOBUTILO KETONA, Y RESINA DE EPOXIA. **ACTIVADOR CONTIENE:** XILENO Y ACETONA. El vapor es perjudicial. **AVISO:** Algunos informes han asociado la sobreexposición laboral repetida y prolongada a solventes con daños permanentes en el cerebro y el sistema nervioso. El uso incorrecto intencional, concentrando e inhalando deliberadamente el contenido del producto, puede ser perjudicial o mortal. Provoca irritación nasal, de la piel y la garganta. Evite el contacto prolongado o repetido con la piel. Es perjudicial si se ingiere. Lávese completamente después de manipular. Mantenga el producto alejado del calor, las chispas y las llamas. **LOS VAPORES PUEDEN CAUSAR COMBUSTION INSTANTANEA.** No fume. Apague todas las llamas y también las llamas piloto, así como las cocinas, los calefactores, los motores eléctricos y otras fuentes de ignición mientras use el producto, hasta que hayan desaparecido todos los vapores. Abra todas las ventanas y puertas para lograr una ventilación cruzada y evitar que se acumulen los vapores. **Utilice solamente con la ventilación adecuada.** No respire el polvo, los vapores ni el rocío. **PRIMEROS AUXILIOS:** Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad experimentada persiste, busque atención médica de inmediato. En caso de ingestión, no induzca el vómito. Busque atención médica de inmediato. En caso de contacto con los ojos o con la piel, enjuague de inmediato con abundante agua durante al menos 15 minutos. Quite la ropa y el calzado contaminados. Busque atención médica de inmediato. Lave la ropa antes de volver a usarla. En caso de derrame, absorbalo con material inerte y deséchelo según las regulaciones aplicables. **ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
EPOXYSHIELD®
PROFESSIONAL FLOOR COATING KIT

PROJECT DETAILS QUICK GLANCE	
BEST FOR	Commercial Garages, Workshops, Warehouses and More
KIT COVERAGE	300 - 400 sq. ft.
# GARAGE	1½ Car
WALK-ON READY	16 Hours
DRIVE READY	4 Days
# COATS NEEDED	1
CLEAN UP	Xylol
APPLY WHEN WEATHER IS	Between 60° F - 100° F

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-481-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

SATISFACCIÓN GARANTIZADA: Si no está satisfecho con este producto, comuníquese con el Soporte Técnico de Rust-Oleum al 800-481-4785 para obtener un reembolso del total del precio de compra. Consulte el número de producto y el código de lote.

1-888-NUFLOOR
(1-888-683-5667)

FOR PROFESSIONAL USE ONLY.
USDA ACCEPTABLE

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 rustoleum.com/epoxyshield
Made in USA / Hecho en E.U.A.
©2017 Rust-Oleum Corporation 334464 1117

CATEGORY
Industrial Maintenance Coating
Max VOC 250 g/l (2.08 lbs./gal.)



• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
EPOXYSHIELD®

NO PEEL PROMISE
Rust-Oleum's trusted quality, guaranteed to produce long-lasting results with no peeling or cracking.

PROFESSIONAL FLOOR COATING KIT

FEATURES & BENEFITS

- Tough, 2-Part Epoxy
- Industrial-Grade Protection for Commercial Applications
- Prevents Concrete Chipping, Cracking, and Dusting Due to Water Absorption
- Forms a Bond that is Stronger than Concrete
- Superior Abrasion, Chemical and Water Resistance
- No Hot Tire Pick-Up

RUST-OLEUM CROSS-LINKING TECHNOLOGY™
Unachievable with One-Part Paints

Network of Crisscrossing Polymer Chains
Ultimate Abrasion, Chemical and Water Resistance
Maximum Hardness and Adhesion

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
EPOXYSHIELD®

NO PEEL PROMISE

PROFESSIONAL FLOOR COATING KIT

2-Part, Solvent-Based Epoxy
Superior Resistance to Chemicals, Standing Water, and Wear from Heavy Traffic
No Hot Tire Pick-Up
Easy to Use and Apply
100% Satisfaction Guaranteed

INDUSTRIAL-GRADE PERFORMANCE

ASK THE PROS
GARAGE FLOOR HOTLINE
888-NUFLOOR

KIT COVERS
300-400 SQ. FT.

Base: 1 Gallon (3.78 L)
Activator: 1 Gallon (3.78 L)

WARNING! FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES SKIN AND EYE IRRITATION. See other cautions on back panel.

SILVER GRAY SEMI-GLOSS

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
EPOXYSHIELD®

NO PEEL PROMISE

PROFESSIONAL FLOOR COATING KIT

2-Part, Solvent-Based Epoxy
Superior Resistance to Chemicals, Standing Water, and Wear from Heavy Traffic
No Hot Tire Pick-Up
Easy to Use and Apply
100% Satisfaction Guaranteed

INDUSTRIAL-GRADE PERFORMANCE

ASK THE PROS
GARAGE FLOOR HOTLINE
888-NUFLOOR

KIT COVERS
300-400 SQ. FT.

WARNING! FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES SKIN AND EYE IRRITATION. See other cautions on back panel.

SILVER GRAY SEMI-GLOSS

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
EPOXYSHIELD®

PROFESSIONAL FLOOR COATING KIT

OTHER SUPPLIES NEEDED

- ☐ Stiff bristle broom or scrub brush
- ☐ Roller frame, tray, solvent resistant cover (¾" nap)
- ☐ Extension pole
- ☐ Squeegee (for the most effective cleaning and to speed drying)
- ☐ Rust-Oleum® Concrete Etch

KIT INCLUDES

- ☐ Rust-Oleum® Heavy-Duty Degreaser
- ☐ Rust-Oleum® Anti-Skid Additive
- ☐ Rust-Oleum® Concrete Patch & Repair

PART A **PART B** **DECORATIVE COLOR CHIPS** **INSTRUCTIONAL SHEET (ENGLISH/ESPAÑOL)**

GARAGES
WORKSHOPS
WAREHOUSES