

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
24 hour Chemtrec International number:* (703) 527-3887 (collect calls accepted.)
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.
Date prepared: 1/08/2008

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (TRADE NAME): #28010 Ford Engine Blue Brushing Lacquer

----- SECTION II - HAZARDOUS INGREDIENTS -----

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
Toluol (Toluene)	108-88-3	5-10	200 ppm.	50 ppm.
Propylene Glycol n-Butyl Ether	5131-66-8	1-5	Not Estab.	Not Estab.
Isobutyl Alcohol	78-83-1	40-45	100 ppm.	50 ppm.
Propylene Glycol Methyl Ether Acetate	108-65-6	5-10	Not Estab.	Not Estab.
Diacetone Alcohol	123-42-2	1-5	50 ppm.	50 ppm.
Butyl Benzyl Phthalate	85-68-7	1-5	Not Estab.	Not Estab.
Titanium Dioxide Pigment	13463-67-7	1-5	15 mg/cu.m.**	10 mg/cu.m.**
Copper Phthalocyanine Pigment	147-14-8	1-5	Not Estab.	Not Estab.
* Stoddard Solvent as Guide		** Total Dust		

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: 220 to 370 deg.F SPECIFIC GRAVITY (Water=1): .940
GALLON WEIGHT OF VAPOR PRESSURE: 9.5 mm Hg @ 20 deg.C (calc.)
PRODUCT (Lbs/Gal): 7.83 VAPOR DENSITY: Heavier than air.
PERCENT VOLATILES EVAPORATION RATE: Slower than Ethyl Ether.
(By Volume): 71.1

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

FLASH POINT (SFCC): 65 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 10.9
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 2 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 1/08/2008

Product Identity: #28010 Ford Engine Blue Brushing Lacquer

----- **SECTION V - SPILL OR LEAK PROCEDURES** -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- **SECTION VI - HEALTH HAZARD DATA** -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? Yes* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or high vapor concentration contact is
extremely irritating and may cause corneal injury.

SKIN CONTACT: Brief contact is not expected to be harmful. Prolonged and
repeated liquid contact can cause defatting and drying of the skin which may
result in skin irritation and dermatitis. Can be absorbed due to prolonged
contact.

BREATHING: Vapors are irritating to nose and throat. High concentrations may
cause nausea, dizziness, drowsiness, headache and unconsciousness.

SWALLOWING: Moderately Toxic. May cause inebriation, nausea, vomiting and
diarrhea.

CHRONIC OVEREXPOSURE: Can lead to central nervous system depression producing
such effects as headache, dizziness, nausea and loss of consciousness.

*Titanium Dioxide component is an IARC Group 2B-Possible carcinogen.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- **SECTION VII EMERGENCY AND FIRST AID PROCEDURES** -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Seek medical attention. Contact a physician, medical facility, or
poison control center for advise about whether to induce vomiting. If
possible, do not leave individual unattended.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 3 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 1/08/2008

Product Identity: #28010 Ford Engine Blue Brushing Lacquer

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.