



**ZINSSER® B-I-N®  
WITH TURBO SPRAY SYSTEM™**

**DESCRIPTION AND USES**

Zinsser® B-I-N® with Turbo Spray System™ combines the power of B-I-N shellac base primer with the speed and convenience of the Turbo Spray System to provide the perfect aerosol solution for priming medium to large sized projects fast. The Turbo Spray System will spray up to 10” wide allowing for faster project completion.

Zinsser B-I-N with Turbo Spray System is great for blocking stains and odors from water, fire, and smoke and is perfect for disaster restoration jobs. It will also block odors from pets, urine, mold & mildew, and cigarettes. B-I-N is a great wood sealer and will sand easily to a powder when dry. It sticks to all surfaces, even ceramic tile & glass. Use on any interior wood, concrete, drywall, or non-galvanized metal.

Zinsser B-I-N with Turbo Spray System can be used under and over most architectural latex and oil based paints.

**PRODUCT**

SKU	DESCRIPTION (26 Oz. Aerosol)
356880	B-I-N White

**PRODUCT APPLICATION**

**READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT**

**SURFACE PREPARATION**

Surfaces should be clean, dry, sound and free of dust, dirt, grime, grease, oil, wax, wallpaper adhesive or any contamination that may interfere with adhesion. Remove loose paint, dirt and rust. Mask off nearby objects.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Use at room temperature (70°F) in a well ventilated area – avoid high humidity. Shake can vigorously until ball inside can rattles. Turn upside down and continue shaking for one minute – shake occasionally during use. If mixing ball fails to rattle, **DO NOT STRIKE** the can. Contact Rust-Oleum®. Hold can upright 8-14” from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. **Do not use near open flame.**

**NOTE:** The closer the can is held to the surface, the faster you should move the can while painting to avoid drips and sags.

**DRY AND RECOAT TIMES**


Surface dries to the touch in 15 minutes and may be painted after 30 minutes.

**CLEAN UP**

To clear spray for future use, turn can upside down and spray until clear gas is emitted. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

**CLOGGING**

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem. Clean up wet paint with xylol or mineral spirits.

	<b>TECHNICAL DATA</b>	<b>BIN-11</b>
	<b>ZINSSER® B-I-N®</b> <b>WITH TURBO SPRAY SYSTEM™</b>	

**PHYSICAL PROPERTIES**

		B-I-N WITH TURBO SPRAY SYSTEM
<b>Resin Type</b>		Shellac and rosin
<b>Pigment Type</b>		Standard
<b>Solvents</b>		3C denatured ethanol, n-butanol, acetone
<b>MIR</b>		0.58 max
<b>Fill Weight</b>		24 oz.
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		2.0-3.0 mils (50-75µ)
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		20-24 sq. ft./can
<b>Dry Times at 77°F (25°C) and 50% Relative Humidity</b>	<b>Touch</b>	9 minutes
	<b>Handle</b>	44 minutes
	<b>Recoat</b>	Any time after 30 minutes
	<b>Full Cure</b>	7 days
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-141°F (-96°C)
<b>Shelf Life</b>		5 years
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.