



TESTORS® ALL PURPOSE CHROME CRAFT SPRAYS

DESCRIPTION AND USES

Testors® All Purpose Chrome Craft Sprays work great on many surfaces. All Purpose Chrome Craft Sprays have a bright reflective finish, dry quick and are great for indoor or outdoor applications.

NOTE: Test before using on project.

PRODUCTS

SKU	DESCRIPTION (3 Oz.)
352617	Chrome Silver
352658	Chrome Black

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants. Rinse with fresh water and allow to thoroughly dry.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Shake can vigorously for one minute before use and shake often. Hold can 10" to 12" from work. Chrome effect is best on smooth, unscratched surfaces. A gloss basecoat is recommended for matte and porous surfaces. Spray in multiple thin coats to achieve chrome look. Apply a second coat anytime. Continuously spray, DO NOT stop in middle. Spray past object being painted.

DRY AND RECOAT TIMES

Based on 77°F 25°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 10 minutes, to handle in 30 minutes, recoat anytime and fully cured in 24 hours.

COVERAGE

Up to 4 sq. ft. per 3 ounce aerosol.

CLEAN-UP

If nozzle clogs, clean with lacquer thinner.

PHYSICAL PROPERTIES

		TESTORS CHROME CRAFT SPRAYS
Resin		CAB
Pigment		Varies by color
Solids By Volume		1.58%
VOC		780 g/l
Recommended Dry Film Thickness (DFT) per Coat		1 mil
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	10 minutes
	Handle	30 minutes
	Recoat	anytime
	Full Cure	30 minutes
Shelf Life		3 Years
Flash Point		-141°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.