

Testors Craft Glitter Fabric spray paints gives fabrics a radiant sparkle finish. Use for full, even coverage or with a stencil. Glitter finish does not come off when touched. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days. To preserve glitter finish, items may be machine washed up to 5 times.

Directions: Use at room temperature 70°F (21°C) and humidity is below 65%. Shake can vigorously for one minute before using and re-shake often during use. Do not apply product to a project while wearing. If using a stencil, cover the areas of the project that are not being painted on to avoid over-spray. Spray can 6"– 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120°F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. **Avoid contact with eyes, skin and clothing.** Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.** **CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint Glitter



Gold
GLITTER

DRIES SOFT

NO HEAT SEAL REQUIRED

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

RUST-OLEUM
CORPORATION
11 Hawthorn Pkwy, Vernon Hills, IL 60061
800-837-8677 rustoleum.com/testors
Made in USA
©2020 Rust-Oleum Corporation 362952 0220

353835



0 20066 46635 0

NET WT. 5OZ (142g)

Testors Craft Glitter Fabric spray paints gives fabrics a radiant sparkle finish. Use for full, even coverage or with a stencil. Glitter finish does not come off when touched. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days. To preserve glitter finish, items may be machine washed up to 5 times.

Directions: Use at room temperature 70°F (21°C) and humidity is below 65%. Shake can vigorously for one minute before using and re-shake often during use. Do not apply product to a project while wearing. If using a stencil, cover the areas of the project that are not being painted on to avoid over-spray. Spray can 6"– 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120°F. **NOTICE:** INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. **Avoid contact with eyes, skin and clothing.** Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.** **CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint Glitter



Silver
GLITTER

DRIES SOFT

NO HEAT SEAL REQUIRED

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5OZ (142g)

RUST-OLEUM
CORPORATION
11 Hawthorn Pkwy, Vernon Hills, IL 60061
800-837-8677 rustoleum.com/testors
Made in USA
©2020 Rust-Oleum Corporation 362953 0220

358386



0 20066 46636 7

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT.
Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347309 0119

344363



0 20066 43662 9

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347308 0119

344362



0 20066 43661 2

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347307 0119

344361



0 20066 43660 5

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347306 0119

344360



0 20066 43659 9

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344357



0 20066 43656 8



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347304 0119

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. **Do not puncture or incinerate (burn) container.** Exposure to heat or prolonged exposure to sun may cause bursting. **Do not expose to heat or store at temperature above 120° F.** NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236.** For emergency health information, call your Poison Control Center 1-800-222-1222.

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347305 0119

344359



0 20066 43658 2