

DO NOT USE THIS OUTPUT TO MATCH PANTONE COLORS.
Use previously approved Pantone Matching Standards
for all PMS color references.

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

TEXTURED



**STOPS
RUST®**

FINE TEXTURED FINISH

Indoor/Outdoor • Works on Metal, Wood & More

WITH COMFORT TIP



DANGER! EXTREMELY FLAMMABLE.
 VAPOR HARMFUL. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.

See other cautions
on back panel.

NET WT. 12 OZ. 340g

Observar otras precauciones
al dorso.

¡PELIGRO! EXTREMADAMENTE INFLAMABLES. VAPORES NOCIVOS. PUEDEN CAUSA UN INCENDIO INSTANTANEO REPENTINO. NO SOMETER A PRESION.

RUST-OLEUM TEXTURED features a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying.

Painting Conditions: Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F and 90°F (10°-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Preparation: Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Priming: Use of a Stops Rust® Primer provides added corrosion protection, superior adhesion and hiding and is especially recommended for bare wood and metal.

Painting: Shake vigorously for one minute after mixing ball begins to rattle. Shake often during use. Hold at upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

Dry & Recoat Times based on 70° - 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes, to handle in 1-2 hours and fully dry in 48 hours. Primers may be top coated immediately. Apply a second coat or clear coat within 1 hour or after 48 hours.

Clean-up: When finished spraying, clean spray valve by turning upside down and pushing spray button for 5 seconds. Clean up wet paint with Xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

Clogging: If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.

CONTAINS ACETONE AND XYLENE. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Do not puncture, strike or otherwise (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, wear respiratory protection (NIOSH-approved) or leave the area. Avoid contact with eyes, skin and clothing.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. **WARNING:** This product contains a chemical known to the state of California to cause birth defects, cancer or other reproductive harm. KEEP OUT OF REACH OF CHILDREN. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800) 481-4765. Conforms to ASTM D-4236.

ADVERTENCIA.

CONTIENE ACETONA Y XILENO. Vapores dañinos. Pueden afectar al cerebro o al sistema nervioso causando mareos, dolores de cabeza, o náuseas. Causan irritaciones en los ojos, piel, nariz y la garganta. No perforar, golpear o incinerar (quemar) el contenedor. Una exposición al calor o una prolongada exposición al Sol puede causar ruptura explosiva. No exponga al calor o almacene en temperaturas sobre 48°C (120°F). **AVISO:** Los reportes han asociado una exposición excesiva ocupacional repetida y prolongada a los solventes con daños permanentes al cerebro y al sistema nervioso. Un mal uso intencional al deliberadamente concentrando y respirando el contenido puede ser dañino o fatal. **Los vapores pueden encenderse explosivamente.** Mantenga lejos del calor, chispas y llamas. No fume. Apague las llamas y llamas pilotos, y apague las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición hasta que todos los vapores hayan desaparecido. Prevea la acumulación de vapores abriendo todas las ventanas y puertas para lograr una ventilación cruzada. **Use solamente cuando existe una ventilación adecuada.** No respire el polvo, los vapores o la niebla del rociado. Asegure la entrada de aire fresco durante la aplicación y el secado. Si experimenta lagrimeo de los ojos, dolores de cabeza, o mareos, use protección para la respiración (aprobada por NIOSH) o salga del área. Evite contacto con los ojos, piel y ropa. **Primero Auxilio:** Si es que surge una dificultad al respirar, obtenga la salida del área para obtener aire fresco. Si continua sufriendo una dificultad al respirar obtenga inmediatamente asistencia médica. En caso de contacto con los ojos, enjuague inmediatamente con bastante agua por 15 minutos por lo menos y obtenga atención médica. Para contacto con la piel, lave con agua completamente con jabón y agua.

ADVERTENCIA. Este producto contiene un producto químico que es reconocido en el estado de California por haber causado defectos de nacimiento u otros daños reproductivos. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. En caso de emergencia, comuníquese con su médico, centro local para el control de venenos o clínica para emergencias. Para obtener más información sobre el producto y los posibles efectos en la salud, llame al (800) 481-4785. Conforma con ASTM D-4236. PROHIBIDA SU VENTA A MENORES DE EDAD; PRODUCTO ORIGINARIO DE E.U.A.

- Please recycle when empty
- Complies with governmental MIL standards
- Contains no CFC's or other substances which deplete the ozone layer

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact our Customer Service Department for a full refund of the purchase price. Refer to product number and batch code on bottom of can.

SATISFACCÓN GARANTIZADA: Si no está satisfecho(a) con este producto, haga favor de ponérse en contacto con nuestro Departamento de Atención al Cliente para el reembolso completo del precio de compra. Refiérase al número del producto y al código de lote en la parte inferior de la lata.

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy, Vernon Hills, IL 60061

rustoleum.com

An RPM Company

paintideas.com

1-800-481-4785

©2009 Rust-Oleum Corporation Made in USA Hecho en E.U.A. 251186 0409