

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344363



0 20066 43662 9



Fabric Paint



blue

DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347309 0119

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344362



0 20066 43661 2

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347308 0119



Fabric Paint



pink

DRIES SOFT
NO HEAT SEAL REQUIRED
WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT.
Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

▲WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344361



RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-837-8677 rustoleum.com/testors
Made in USA

©2019 Rust-Oleum Corporation 347307 0119



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT.
Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344360



0 20066 43659 9

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-837-8677 rustoleum.com/testors

Made in USA

©2019 Rust-Oleum Corporation 347306 0119



Fabric Paint



red

DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT.

Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" – 12" (15 cm – 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

344357



RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-837-8677 rustoleum.com/testors
Made in USA

©2019 Rust-Oleum Corporation 347304 0119



Fabric Paint



DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT.
Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

Testors Craft Fabric spray paint, transforms fabrics into a personalized piece with a touch of color. Use for full, even coverage or with a stencil. Try blending colors when wet or add color over another when dry for a more dramatic effect. Machine washable, so colors stay true wash after wash. No heat setting required. Works great on a majority of fabrics, including clothing, canvas bags, shoes, pillows, small furniture or cushions. Dry to the touch in less than 30 minutes; dry to handle in 3 hours; washable in 3 days.

Directions: Use at room temperature 70°F (21°C) and humidity is below 60%. Shake can vigorously before using and reshake often. Do NOT apply product to a project while wearing. Spray can 6" - 12" (15 cm - 31 cm) from work. Spray with continuous motion. Apply 2 or more light coats a few minutes apart. Turn can upside down after use and spray 5 seconds to prevent clogging.

Painting Conditions: Use in a well-ventilated area. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

CONTAINS: Dimethyl ether, ethanol. Vapor harmful. Vapors may ignite explosively and accumulate readily. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin, nose and throat irritation. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperature above 120° F. NOTICE: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mist. Wash thoroughly after use. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and other sources of ignition during and after use. **Use with adequate ventilation.** To avoid breathing vapors and mist, open windows and doors or use other means to ensure fresh air entry during application and drying. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air, get medical attention immediately. In case of eye contact, flush thoroughly with plenty of water and get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN. CONFORMS TO ASTM D-4236. For emergency health information, call your Poison Control Center 1-800-222-1222.**

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.



Fabric Paint



white

DRIES SOFT

NO HEAT SEAL REQUIRED

WASHABLE / PERMANENT

⚠ DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. CONTAINER MAY EXPLODE IF HEATED. CONTENTS UNDER PRESSURE. EYE IRRITANT. Read cautions carefully on back panel.

NET WT. 5 OZ. (142g)

344359



RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-837-8677 rustoleum.com/testors
Made in USA

©2019 Rust-Oleum Corporation 347305 0119